

Orchard 120

Satusteam™ Applicator Head

The Orchard 120 is designed to be towed behind or beside vehicles for treating weeds along orchard plantation rows, covering a swept path width of 120 cm.

The Orchard 120 has a 6000 series aluminium chassis with puncture-proof castor wheels to maintain optimal height above ground level to maximise application speed.



The hood is fabricated of a light weight insulated aluminium sandwich material that helps retain heat. The Orchard 120 frame has a mounting point where a Rowtech 55 can be attached, to provide a means of weeding the stretch between tree trunks.

The Ultimate Solution in Organic Weed Control

For Use With



SW 900 (Single)



SW 3800KD (Double)

Orchard 120

- Specialized steam delivery manifold and nozzles for optimum spread and saturation
- Insulated, robust and lightweight construction
- Low profile design for under canopy work
- 120 cm (4') treatment span
- Left or right hand side mounting



One Day After Treatment

ORCHARD 120			Flow Rate: 12 L/min (3 gal/min)					
			Weight: 30 Kg (66 Pound)					
			*Note: Consumption figures are a guide only.					
Width			Length			Height		
mm	cm	inch	mm	cm	inch	mm	cm	inch
1200	120	47	1050	105	41	305	30.5	12

**Queensland
Distributor**

Kinan Lemberg, Director
 Mobile: 0477 786 847
www.bluehandsteam.com.au
kinan@bluehandsteam.com.au

